

ALUMINUM ELECTROLYTIC CAPACITORS

STANDARD RATINGS

Cap(μF)	VV(v)	160		200		250	
		Size	Ripple	Size	Ripple	Size	Ripple
		ΦDXL(mm)	mArms	ΦDXL(mm)	mArms	ΦDXL(mm)	mArms
2.2	--	--	--	--	10x12.5	26	
3.3	--	--	--	--	10x12.5	31	
4.7	--	--	--	--	10x16	42	
6.8	10x12.5	45	10x12.5	45	10x16	51	
10	10x16	62	10x16	62	10x20	68	
22	10x20	101	10x20	101	12.5x20	113	
33	12.5x20	139	12.5x20	139	12.5x25	153	
47	12.5x20	165	12.5x20	165	16x25	207	
100	16x25	302	16x25	302	18x31.5	346	
220	18x31.5	514	18x31.5	514	18x35.5	550	
330	18x35.5	673	18x35.5	673	--	--	

Cap(μF)	VV(v)	350		400		450	
		Size	Ripple	Size	Ripple	Size	Ripple
		ΦDXL(mm)	mArms	ΦDXL(mm)	mArms	ΦDXL(mm)	mArms
1.0	--	--	10x12.5	16	10x12.5	16	
2.2	10x16	26	10x16	26	10x16	26	
3.3	10x16	32	10x16	32	10x16	32	
4.7	10x20	42	10x20	42	10x20	42	
5.6	10x20	46	10x20	46	12.5x20	51	
6.8	12.5x20	56	12.5x20	56	12.5x20	56	
10	12.5x20	68	12.5x20	68	12.5x25	75	
22	12.5x25	112	12.5x25	112	16x25	127	
33	16x25	155	16x25	155	16x31.5	168	
47	16x31.5	201	16x31.5	201	18x31.5	212	

Ripple Current(mA rms) at 125°C, 120Hz