

ALUMINUM ELECTROLYTIC CAPACITORS

■ STANDARD RATINGS

Rated voltage 6.3V			
Rated capacitance (μ F)	Size Φ DXL (mm)	Rated ripple current (mA r.m.s./105°C, 100KHz)	ESR ($m\Omega$ max/20°C, 100KHz)
820	8x11.5	1140	36
1200	8x16	1490	28
1800	8x20	1870	19
1500	10x12.5	1540	26
1800	10x16	2000	19
2200	10x20	2550	13
3300	10x25	2800	12

Rated voltage 10V			
Rated capacitance (μ F)	Size Φ DXL (mm)	Rated ripple current (mA r.m.s./105°C, 100KHz)	ESR ($m\Omega$ max/20°C, 100KHz)
680	8x11.5	1140	36
1000	8x16	1490	28
1500	8x20	1870	19
1000	10x12.5	1540	26
1500	10x16	2000	19
1800	10x20	2550	13
2200	10x25	2800	12

Rated voltage 16V			
Rated capacitance (μ F)	Size Φ DXL (mm)	Rated ripple current (mA r.m.s./105°C, 100KHz)	ESR ($m\Omega$ max/20°C, 100KHz)
470	8x11.5	1140	36
680	8x16	1490	28
1000	8x20	1870	19
1500	10x12.5	1540	26
1000	10x16	2000	19
1500	10x20	2550	13
1800	10x25	2800	12